

What is claimed is:

1. A crystal oscillator, comprising:

an oscillation unit comprising a crystal vibrator
5 having a frequency-temperature characteristic with
which a resonance frequency changes according to a
temperature, and an oscillation circuit unit; and

a heat source unit, which abuts against the
crystal vibrator, keeping a temperature of the crystal
10 vibrator higher than a temperature where the crystal
vibrator causes abnormal oscillation.

2. The crystal oscillator according to claim
1, wherein

15 the crystal vibrator is kept at a temperature
higher than 0 °C.

3. The crystal oscillator according to claim
1, wherein

20 said heat source unit is configured by a power
transistor which amplifies an oscillation output.

4. The crystal oscillator according to claim
1, wherein

25 said heat source unit is configured by a power

transistor which configures a power supply.

5. The crystal oscillator according to claim
1, wherein

5 the abnormal oscillation is caused by a micro-jump
which occurs in the crystal vibrator.

6. A crystal oscillator, comprising:
an oscillation unit having a crystal vibrator; and
10 a heat source unit keeping a temperature of the
crystal vibrator higher than a temperature where the
crystal vibrator causes abnormal oscillation.

7. The crystal oscillator according to claim
15 6, wherein

said heat source unit keeps the crystal vibrator
at a temperature higher than 0 °C.

8. The crystal oscillator according to claim
20 6, wherein

said heat source unit is configured by a power
transistor.

9. The crystal oscillator according to claim
25 8, wherein

said heat source unit is configured by a power transistor which amplifies an oscillation output.

10. The crystal oscillator according to claim
5 8, wherein

said heat source unit is configured by a power transistor which configures a power supply.

11. The crystal oscillator according to claim
10 6, wherein

the abnormal oscillation is caused by a micro-jump which occurs in the crystal vibrator.

12. The crystal oscillator according to claim
15 6, further comprising

a control unit controlling heat generated by said heat source unit based on a temperature of the crystal vibrator.

13. A crystal oscillator, comprising:
20 oscillation means having a crystal vibrator; and
heat source means for keeping a temperature of the crystal vibrator higher than a temperature where the crystal vibrator causes abnormal oscillation.

25

14. A signal oscillation method preventing abnormal oscillation of an oscillator having a crystal vibrator, comprising:

5 keeping a temperature of the crystal vibrator higher than a temperature where the crystal vibrator causes abnormal oscillation; and

outputting a signal in a state where the temperature is kept.

10054331 012322